

Shaking Ultra Sonic Water Bath / SONOSHAKE



Wiggens shaking ultrasonic water bath SONOSHAKE has the function of ultrasonic cleaner and shaking water bath, SONOSHAKE offers a wide range of possible applications for sample preparation in many areas of analysis, for example, in environmental and foodstuffs analytics as well as in the area of medical diagnostics.

Both procedures can be carried out simultaneously or separately.

This means that a sample can be pre-homogenized at a specified shaking frequency, and then final homogenization can be achieved in a very short time using ultrasound.



- Analogue setting of time (1–15min or continuous) and shaking frequency
- Reciprocating motion: settings in 4 steps possible of up to 200 shakes/min
- Constant amplitude of 20 mm independently of loading
- Rack easy to remove
- Fast mounting of the laboratory clamps EK 10 –250 (ordering separately)
- Shaking platform approx. $480 \times 280 \text{ mm} (I \times w)$
- The ultrasonic frequency is 35/53Hz
- Heating range is 20-80C
- Oder NO.: WSA1028

WIGGENS GmbH	WIGGENS China
Gässlesweg 22-24, 75334 Straubenhardt, Germany	Room 426, Hall A, Office Building M8, No.1 Jiuxianqiao East
Tel.: 0049 7248 4529088	Road, Chaoyang District, Beijing 100015, China
	Tel: +86 400-809-2068
	Fax: +86 400-809-2068-112
	Email: info@ wiggens.com service@wiggens.com
	Website: www.wiggens.com